

The Chi-Namel Ready-to-use Graining System can be successfully applied by any inexperienced person. Saves money for the painter and assists him in producing a perfect grain. It completely hides the color and blemishes in old flooring, and gives a finish which has the color, grain effect and wearing quality of new hard wood.

No old floor so hlack, so rough that the Chi-Namel Graining System cannot make it suitable to use with rugs. Same effect may also he applied to cement floors. Make the old carpet into rugs, and give your floors the New Chi-Namel finish and be up-to-date.

Costs only 2c per square ft.

Directions for Graining

. Apply Graining First Coater-Allow it to dry over night, next day apply Graining Compound and immediately draw Self-Grainer through the Con-pound. Compound will dry in 15 minutes, after

which Natural or any of the colored transparent Chi-Namel Varnisbes may be applied.

Chi-Namel Graining Sets

With which any amateur can reproduce the grain of natural wood as shown above. natural wood as snown above.
Set No. 1, (3 inch width),... price with Comh
Set No. 3, (5 inch width),...
For quarter-sawed effect, Set No. 5, price with Comb.......

Rubber Comb "C" each

Chi-Name! Stippling Brush, each To be used in whipping Chi-Namel

Graining Compound to give a stippled effect on floors, doors, etc.

Corner and Border Stencil Set No. 1 For producing the inlaid hardwood effect on Chi-Nameled floors.

Crack Filler 1 Gal. 1/2 Gal. Ot. Pt. 1/2 Pt. 1/4 Pt.

Graining First Coater
(Lt. or Dk.) For preparing surfaces for graining with Chi-Namel
Graining Compound, Opaque and hides all defects.

Graining Compound—Light, Medium or Dark,
To be applied over Graining First Coater. The wood grain is outlined in it with Chi-Namel Self-Grainer while coating is wet. To be followed with Chi-Namel Varnish.

Floor Outfits Containing all tools and material to grain, stain and varnish one average size floor.

Directions For Chi-Nameling New Wood

Chi-Namel Penetrating Stain if used, must be applied to the bare wood and allowed 24 hours for drying.

Coarse Grained Wood, such as ash, oak, chestnut, walnut, mahogany, etc. After the Penetrating Stain, apply Chi-Namel Paste Filler, (directions on each package). Allow 24 hours to dry, then finish with Chi-Namel Varnish.

nnish with Chi-Namel Varnish.
Close Grained Wood, such as pine, whitewood, cypress, fir, maple, etc. After the Penetrating Stain apply Chi-Namel Clear First Coater (except for exterior surfaces). If this is not at hand use Chi-Namel Natural Varnish. Do not use Shellac.
Varnish should be selected with reference to the kind of service re-

quired, as follows;
Floors, Chi-Namel Natural Varnish, two coats in addition to Clear
First Coater, 24 hours apart for gloss finish.

Upright Surfaces, such as doors, wainscotings, mantels, hase hoards, etc. Chi-Namel Heavy Interior Varnish in addition to Chi-Namel Clear First Coater, for gloss finish.

Exterior Surfaces, Chi-Namel Exterior Spar Varnish, three coats

48 hours apart.

Egg Shell Gloss, ruh final varnish coat with Chi-Namel Shine Easy and Chi-Namel Rub Easy on a soft cloth.

Dead or Dull Finish, rub final varnish coat with water and Chi-Namel Rub Easy on a soft cloth—or coat with Chi-Namel Dull Natural Varnish.

Waxed Finish, apply Chi-Namel Prepared Wax over Chi-Namel Varnish for floors and apply over Wax Like finish for upright work or furniture and rub with dry cloth. Durable Mission Finish, apply Chi-Namel Wax-Like over Chi-Namel Penetrating Stain.

To Re-Varnish Previously Finished Wood

Clean with washing powder and rinse well; when thoroughly dry apply Chi-Namel Varnish. For hest results, remove old finish with Chi-Namel Varnish Remover and finish as directed for new wood.

To Restore the Old Color, use Chi-Namel Colored Varnish.

To give new lustre without changing color, use Chi-Namel Natural Varnish.

Chi-Namel A Finish for Everything about the Home For Sale by



Sole Manufacturers

CLEVELAND, O. U.S.A.

Chi-Namel

Cheapest by the yard-because a gallon covers one-third more surface than any other varnish.

Cheapest by the day—hecause it takes a third less time on the part of workmen to brush it upon a given surface.

The reason is, it is made of the hest materials that make varnish, hard gum and specially treated oils, so that extreme toughness, elasticity and water resisting qualities result. Hammer it, scratch it or holi it; it will neither turn white nor lose its gloss. Best for new huildings; hest for old ones.

For furniture or any wood or metal surface.

Architectural Varnishes—Clear

1 Gal ¼ Gal. Qt. Pt. ½ Pt. ¼ Pt. 14 Pt. sq. ft. sq. ft.

COVERING CAPACITY-2 Coats Natural Varnish

For new or old floors, furniture, woodwork, linoleum, etc. Heavy Interior

For upright interior surfaces of new huildings. Same quality as Natural hut heavier hody. Not to he used on floors.

Dull Natural

Gives a dull effect resembling a rubbed finish when applied over a stained or gloss surface.

Wax-Like

A varnish that gives the effect of a wax finish but contains no wax. **Exterior Spar** For outside doors, boats and other surfaces exposed to weather.

Marine Spar

Made especially for hoats and other surfaces that are continuously

suhmerged in water. Clear First Coater

To he used in place of Shellac, Pigment Surfacer or other first coating preparations, on new woodwork hefore finishing.

Auto and Carriage Varnishes—Clear

Pale Wearing Body

For finishing coats on bodies of high grade vehicles, such as carriages, automobiles, etc. May he used over light colors.

Heavy Gear

For finishing coat on gears of high grade vehicles. Pale Carriage Rubbing

For under coats on high grade vehicles.

Clear Carriage For finishing or refinishing hodies and running parts of all vehicles, except over gray or very light colors.

Chi-Namel Carriage and Auto Color Finishes

Black-Blue Brown-Yellow

Vermillion-Wine-Carmine

Permanent Green-Brewster Green-

Lt. & Dk. Gray Give new color and hrilliant gloss to old vehicles. Very durahle. Non-fading and easily applied. For new work or hadly cracked surfaces use Auto Under Coat hefore applying. Full directions on package. Colored Varnishes-Transparent

Gloss Chi-Namel Varnish

DISS CHI-IVAINEL VALUES AND ALGER OAK—DARK OAK—Mahogany—Walnut—Rosewood. Give a hrilliant gloss—stain and varnish in one application. One coat makes old furniture or woodwork as good as new.

Golden Oak-Cherry-

Satinwood

White Enamels-Opaque

Ever White Enamel

For interior trim of fine residences, hotels, hospitals, colleges, schools, husiness houses, flats, hanks, steamships, etc. For exterior as well as interior use.

For interior trim of huildings, where a sott, velvet-like surface is desired. Washahe with soap and water.

Interior White Ename!

For interior trim of huildings where quicker work is required.

Resistol White Enamel

For interior woodwork, furniture. hric-a-brac, etc.

White Bath Tub Enamel For enameling hatb tuhs, refngerators, kitchen sinks and wood-work surrounding same. Absolutely waterproof.

Colored Enamels-Opaque

Red Green-Willow Green-Wicker Brown-Black

For porch, lawn and park furniture, fences, flower stands, bicycles, pumps, wheelharrows, children's wagons, toys, or other exterior use.

Med. Blue-Lt. Green

For interior use such as heds, dressers, woodwork, etc.

Flat Black Dense, dull hlack-gives a wrought iron effect on wood or metal.

Dull Wall Enamel A flat washahle wall coating. Easy to apply, May be cleaned with soap and water. (See special Wall Enamel card for colors.)

1 Gal. 12 Gal. Qt. Pt. 12 Pt. 14 Pt. sq. ft. sq. ft. sq. ft. sq. ft. sq. ft. sq. ft. 400 200 100 50 25 13 COVERING CAPACITY -2 Coats

Stove Pipe Enamel

Dense glossy hlack—withstands heat remarkably. Prevents rust on stove and furnace pipes, stoves, etc.

Screen Enamel-Green

Black

Easy to apply to wirecloth—does not clog the meshes. Makes old screening look like new — prevents rust. Should be used for economy if for no other reason.

First Coaters

Graining First Coater

(Flat Yellow)—Light or Dark—Opaque—For preparing old, hlack, stained surfaces for graining with Chi-Namel Graining Compound.

Superior to Shellac or liquid wood filler for new wood that is to he finished with Chi-Namel Varnish.

Wall First Coater_

To be used with Dull Wall Enamel for sealing coat on walls.

White First Coater

(Flat White) -To prepare surface for coating with White Enamel.

Auto Under Coat

For new wood and old surfaces that are hadly checked.

Black—Yellow Red—Gray

Miscellaneous

Penetrating Stains

Mah. & Dark Mahogany

Other Colors

For staining new wood.

Leather Top Dressing

For renewing the color and gloss of leather or imitation leather tops of autos and carriages. Black, elastic and durable.

Mohair Top Dressing

For renewing mohair tops of autos, motor hoats, etc.

Shine-Easy

The Chi-Namel furniture polish. Cleans and revives the lustre and also acts as a food for varnish, thus prolonging its life. Also for dusting and for dust mops.

each Rub-Easy, (In Sifter Top Cans) A polishing powder for varnish, removes stains produced by water, heat, alcohol, medicine, etc.

Metal-Glow

For polishing all metals, such as Brass, Nickel, Copper, Steel, etc.

Varnish Remover

Chi-Namel Stencils

In decorative designs for walls. See Chi-Namel Stencil Book.

Glazing Liquid

Cementone-In colors and colorless. For waterproofing and decorating cement bouses, floors, foundations, etc. For prices and colors see Cementone Color Card.

Shingle Stain - For preserving and heautifying shingles and any rough wood. See Shingle Stain Color Card for prices.

Paste Filler

21b., 31b 1b. 5 lb. 1b. 10th. :1b, 25lb. 1 lb.

For closing the pores of coarse grained woods before varnishing, when a perfectly smooth varnish surface is desired. Made in four colors—Light—Dark—Golden Oak—Mahogany.

1 lb., 2 lh. 4 lb., 8 lh. 1/2 lb. 1/2 lh.

Prepared Wax


For floors, and also excellent for furniture, woodwork and all varnished or stained surfaces.

Dance Floor Wax-For private and public dance floors

Gold Paint				Aluminum Paint			
Size	Price.	Size	Price	Size	Price	Size	Price
475		75		250		45	
250		45		135		30	
135		25		75		20	
Fo	r radiato	rs, gas	fixtures,	moulding,	bric-a-hr	ac, etc.	
				Gal.	1,5	Gal.	Ot.

per lb. Aluminum Bronze ½ lb. Bronzing Liquid..... Gold Bronze

per lb. 2 lb.



CHI-NAMEL AUTOMOBILE COLORS—One coat of any of these colors will hide the old color and give a beautiful, brilliant, durable surface like new. Easy to apply, and owing to the Chinese Oil used in them, are tough and elastic, as well as quick-drying and water-proof. Instructions on each package.

CHI-NAMEL AUTOMOBILE COLORS





CHI-NAMEL OPAQUE (SOLID-COVERING) ENAMELS—In White and Colors. For exterior and interor use, as iindicated in instructions. CHI-NAMEL GRAINING FIRST COATER—To hide blemishes in old or defective woodwork preparatory to applying Chi-Namel Graining Compound.

CHI-NAMEL ENAMELS, ETC.





CHI-NAMEL TRANSPARENT VARNISHES give new color and new gloss with one application. Easy to apply;—dry over night. For floors, doors, stairs, linolcums, wainscotings, tables, chiffoniers, dressers, bodsteads, book-cases, desks, settees, refrigerators, etc. The original hammer-proof and water-proof finishes.

CHI-NAMEL VARNISH-TRANSPARENT





CHI-NAMEL PENETRATING STAINS-FOR NEW WOOD. May be finished with gloss varnisb, or a durable mission effect secured by applying Chi-Namel Wax-Like over the Stain coat. For a wax finish Chi-Namel Prepared Wax may be applied over the Wax-Like.

CIII-NAMEL PENETRATING STAINS



Chi-Namel

Cheapest by the yard-because a gallon covers one-third more surface than any other varnish.

Cheapest by the day—because it takes a third less time on the part of workmen to brush it upon a given surface.

The reason is, it is made of the best materials that make varnish, hard gum and specially treated oils, so that extreme toughness, elasticity and water resisting qualities result.

Hammer it, scratch it or boil it; it will neither turn white nor lose its gloss. Best for new buildings; best for old ones.

For furniture or any wood or metal surface.

Architectural Varnishes—Clear

1 Gal 1/2 Gal. Qt. Pt. 1/2 Pt. 1/4 Pt.

1 Gal. 12 Gal. Qt. Pt. 12 Pt. 14 Pt. sq. ft. sq. ft. sq. ft. sq. ft. sq. ft. sq. ft. 400 200 100 50 25 13 COVERING CAPACITY-2 Coats

Stove Pipe Enamel

Dense glossy black—withstands heat remarkably. Prevents rust on stove and furnace pipes, stoves, etc.

Screen Enamel-Green

Black

Easy to apply to wirecloth-does not clog the meshes. Makes old screening look like new - prevents rust. Should be used for economy if for no other reason.

First Coaters

Graining First Coater

g old, black, Compound. that is to be

Natural For ne Heavy Ir

Digitized by

walls.

ite Enamel.

ASSOCIATION FOR PRESERVATION TECHNOLOGY. INTERNATIONAL

s the lustre s life. Also

leather tops

www.apti.org

each ed by water,

BUILDING TECHNOLOGY **HFRITAGE** LIBRARY

, Steel, etc.

l Book. : and decor-

les and any

lb.

lb.

Price

Qt.

25 lb.

https://archive.org/details/buildingtechnologyheritagelibrary

school Dead W desire

COVERING

For un Natur

a stair Wax-Lik A vari Exterior For or Marine S Made subme Clear Fir To be coatin Pale We

For fit riages Heavy G

For fit Pale Car

For un Clear Ca

For fir excep!

Chi-

Carm

surfac packa

Light Give a coat n

Rlack-I

Permano Lt. & Non-f

Gloss Ch

Golden (Satin

Ever Wh For it

Brown Vermilli

Dull Nat Gives

Interior For in Resistol

Med. Blue-Lt. Green

For porch, lawn and park furment,

For in White B For er work

Red GreenFrom the collection of:

Jablonski Building Conservation

www.jbconservation.com

ade in four 4 lb., 8 lb.

varnishing.

ind all var-

Paint

ze 45 45 135 30 250 20 25 75 135

For radiators, gas fixtures, moulding, bric-a-brac, etc. Gal.

per lb.

Dense, dull black—gives a wrought iron effect on wood or metal.

Dull Wall Enamel

pumps, wheelbarrows, children's wagons, toys, or other exterior use Pink-Lt. Blue-

For interior use such as beds, dressers, woodwork, etc.

A flat washable wall coating. Easy to apply. May be cleaned with soap and water. (See special Wall Enamel card for colors.)

Bronzing Liquid per lb. Aluminum Bronze

2 1b.